

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) A data processing device having a first operational mode and a second operational mode, the data processing device comprising:

a plurality of control elements to perform a first plurality of defined functions when the data processing device is in the first operational mode and to perform a second plurality of defined functions when the data processing device is in the second operational mode, wherein:

the first operational mode is associated with a first physical orientation of the data processing device and the plurality of control elements; and

the second operational mode is associated with a second physical orientation of the data processing device and the plurality of control elements, wherein at least one of the plurality of control elements includes:

a first glyph representing a designated one of the first specified functions, the first glyph being highlighted when the data processing device is in the first operational mode; and

a second glyph representing a designated one of the second specified functions, the second glyph being highlighted when the data processing device is in the second operational mode, wherein the data processing device automatically highlights the first glyph when in the first operational mode and automatically highlights the second glyph when in the second operational mode.

2. (Original) The data processing device as in claim 1 further comprising:  
a display having a viewable display screen for rendering images  
generated by the data processing device, the display screen rendering images in  
a first orientation when the data processing device is in the first operational mode  
and rendering images in a second orientation when the data processing device is  
in the second operational mode.

3. (Canceled)

4. (Previously Presented) The data processing device as in claim 1  
wherein each of the first glyphs are positioned on each of the control elements in  
a first orientation corresponding to the first orientation of the data processing  
device and each of the second glyphs are positioned on each of the control  
elements in a second orientation corresponding to the second orientation of the  
data processing device.

5. (Original) The data processing device as in claim 4 wherein the first  
orientation is rotated 90 degrees relative to the second orientation.

6. (Previously Presented) The data processing device as in claim 1  
wherein the first operational mode comprises a data entry mode and wherein the  
second operational mode comprises a telephony mode wherein the data  
processing device performs telephony-based functions.

7. (Original) The data processing device as in claim 6 wherein, when in  
the telephony mode, the second specified function for a group of the control

elements is that of a numeric keyboard for entering telephone numbers.

8. (Original) The data processing device as in claim 7 wherein, when in the data entry mode, the first specified function for a group of the control elements is that of a cursor control keypad.

9. (Original) The data processing device as in claim 1 wherein the plurality of control elements includes a control wheel for moving a graphical cursor element when rotated in either the first operational mode and/or the second operational mode.

10. (Original) The data processing apparatus as in claim 9 wherein the plurality of control elements includes a plurality of keys and/or buttons.

11- 22. (Canceled)

23. (Previously Presented) A data processing device having a first operational mode and a second operational mode comprising:

a first group of control elements to perform a first plurality of defined functions within a first physical orientation and to perform a second plurality of defined functions within a second physical orientation; and

a motion sensor to detect the orientation of the data processing device, wherein the data processing device automatically switches from the first operational mode to the second operational mode in response to the motion sensor detecting the data processing device switching from the first physical orientation to the second physical orientation.

24. (Previously Presented) The data processing device as in claim 23 further comprising:

a display to render images having a first image orientation associated with the first operational mode and to render images having a second image orientation associated with the second operational mode.

25. (Original) The data processing apparatus as in claim 24 wherein the first image orientation is rotated plus or minus 90 degrees with respect to the second image orientation.

26. (Original) The data processing apparatus as in claim 23 wherein the first physical orientation is rotated plus or minus 90 degrees with respect to the second physical orientation.

27. (Previously Presented) The data processing device as in claim 23 wherein the first group of control elements include a first group of glyphs representing the first plurality of defined functions and a second group of glyphs representing the second plurality of defined functions.

28. (Original) The data processing device as in claim 27 wherein the data processing device highlights the first group of glyphs when in the data entry mode and highlights the second group of glyphs when in the telephony mode.

29. (Currently Amended) A data processing device comprising:  
a first plurality of control elements associated with a first plurality of functions, wherein the first plurality of control elements is visible to a user when

the device is in a first orientation, when the device is in a second orientation, and when the device is in a third orientation;

a second plurality of control elements associated with a second plurality of functions, wherein the second plurality of control elements is hidden from a the user when the device is in a the first orientation and when the device is in a the third orientation and the second plurality of control elements is visible to the user when the device is in the second orientation; and

a third plurality of control elements associated with a third plurality of functions, wherein the ~~second~~ third plurality of control elements is hidden from a the user when the device is in the first orientation and when the device is in a the second orientation and the third plurality of control elements is visible to the user when the device is in the third orientation.

30. (Previously Presented) The data processing device of claim 29 wherein:

a first operating mode is associated with the first orientation;  
a second operating mode is associated with the second orientation; and  
a third operating mode is associated with the third orientation.

31– 40. (Canceled)